PLAN VIEW

SIDEWALK RAMP TYPE 4B

PLAN

TOP OF

ROADWAY

DEPRESSED

(SEE NOTE 4)

CURB & GUTTER

5' - 0"

2% MAX.


CEMENT

(SEE STD. PLAN F-30.10)

BUFFER STRIP

SECTION (B


W = 3' - 0" W = 4' - 0" W = 5' - 0" W = 6' - 0" W = 7' - 0" **RADIUS** AT FACE OF CURB X Υ X Υ X Υ X Υ X Υ 20 FEET 4' - 8 1/2" 4' - 1" 3' - 1 1/2" 5' - 5 1/2" 3' - 6 1/2" 5' - 0" 6' - 2 3/4" 3' - 7" 7' - 3 1/2" 8' - 2 1/2" 30 FEET 5' - 9 1/4" 5' - 2 1/2" 4' - 8 3/4" 7' - 3 3/4" 6' - 5 1/2" 7' - 11 1/2" 12' - 3 1/4" 40 FEET 8' - 9 1/2" 7' - 10" 7' - 1" 6' - 5 3/4" 5' - 11 1/2" 15' - 7 1/4" 10' - 5 1/4" 12' - 4 1/2" 14' - 3/4" 8' - 2 1/2" 50 FEET 10' - 3/4" 10' - 3/4" 9' - 1/4" 12' - 7 1/4" 8' - 2 1/2" 14' - 9 1/2" 7' - 6 1/2" 16' - 9" 6' - 11 3/4" 18' - 6 1/4" 60 FEET 10' - 3/4" 14' - 6 1/2" 9' - 2 1/4" 8' - 5 3/4" 7' - 10 1/2" 11' - 2 1/2" 11' - 8 3/4" 16' - 11 3/4" 19' - 1 3/4' 21' - 1 1/2" 70 FEET 12' - 2 3/4" 13' - 3 1/4" 11' - 1/4" 16' - 4" 10' - 1" 18' - 11 3/4' 9' - 3 3/4" 21' - 4 1/4" 8' - 8 1/4" 23' - 6 1/4" 10' - 10 3/4" 80 FEET 13' - 2" 11' - 10 1/2" 10' - 1" 23' - 4 3/4" 9' - 5" 14' - 8 1/2" 17' - 11 3/4" 20' - 10" 25' - 8 3/4" 90 FEET 14' - 1/2" 12' - 8 1/4" 19' - 6 1/2" 11' - 7 3/4" 22' - 7" 10' - 9 3/4" 25' - 3 3/4" 10' - 1 1/4" 27' - 9 1/2" 16' - 1/2" **100 FEET** 14' - 10 1/2" | 17' - 3 3/4" 13' - 5 1/2" 12' - 4 1/4" 11' - 5 3/4" 10' - 9" 21' - 0" 24' - 2 3/4' 27' - 1 1/2" 29' - 9" INTERMEDIATE RADII CAN BE INTERPOLATED



DETECTABLE WARNING PATTERN DETAIL

NOTES

- 1. This layout is used to provide access to a single crosswalk parallel to the major street. The bid item "Cement Conc. Sidewalk Ramp Type 4B" does not include the adjacent Curb (or Curb & Gutter), the Sidewalk, or the Cement Conc. Pedestrian Curb.
- 2. Ramp slopes shall not be steeper than 12H:1V.
- 3. Avoid placing drainage structures, junction boxes or other obstructions in front of ramp access areas.
- 4. Curb & Gutter is shown, see the Contract Plans for the curb design specified. See Standard Plan F-10.12 for curb details.
- 5. See Std. Plan F-30.10 for sidewalk joint placement and details.
- 6. The bottom of the ramp shall have a level area (not in excess of 2% in any direction), 4' × 4'.



5' - 0" RAMP


VARIES:

0 to 6"

BUFFER STRIP

VARIES: 0 to W

TOP OF



SIDEWALK RAMP TYPE 4B WITH LAYOUT

STANDARD PLAN F-40.18-00

SHEET 1 OF 1 SHEET

APPROVED FOR PUBLICATION

Ken L. Smith 02-07-07

